

Artec Spider II

 Artec 3D

Ultra-high resolution target-free handheld 3D scanner



Artec Spider II Specifications



Resolution & accuracy

Resolution, up to	0.05 mm
Accuracy, up to	0.05 mm
3D accuracy over distance, up to	0.05 mm + 0.3 mm/m

Scanning range

Size of scanning object/ area	S–M
Working distance	0.19 – 0.3 m
Volume capture zone	1,800 cm ³
Linear field of view H×W @ closest range	128 × 104 mm
Linear field of view H×W @ furthest range	171 × 152 mm
Depth of field	110 cm

Speed

3D reconstruction rate for real-time fusion, up to	15 fps
--	--------

Scanning algorithms

Target-free technology	Yes
Hybrid geometry and texture tracking	Yes

Texture

Texture resolution	5 MP
Colors	24 bpp

Hardware

Scanner type	Handheld
Power source	AC / DC power adapter, DC 24V
Interface	Thunderbolt 3, compatible with Thunderbolt 4 hosts
3D structured-light source	450 nm LED
Texture illumination source	White LED CRI > 95, color temperature 4000 K
Dimensions HxDxW	187 × 156 × 118 mm
Weight	0.95 kg / 2.1 lbs
Warranty	2 years

Compatibility

Supported OS	Windows 10 (x64), Windows 11
Recommended computer parameters	13th or 14th Gen Intel Core i7 or i9 processors, RTX 4070 8 GB
Minimum computer requirements	12th Gen Intel Core i9 processor, RTX 4060 8 GB

Output formats

3D mesh	OBJ, PLY, WRL, STL, AOP, ASC, PTX, E57, XYZRGB
CAD	STEP, IGES, X_T
Measurements	CSV, DXF, XML

Please note that the specifications for the new Spider II 3D scanner are up-to-date as of the latest prototype testing phase. We reserve the right to modify these specifications as testing and development progress.



Learn more about Artec Spider II
www.artec3d.com



GoMEASURE3D

Official Artec 3D
Gold Status Reseller
Artec 3D Ambassador

GoMeasure3D

158 Second Street
Amherst, Virginia
24521, USA

+1 (434) 946-9125

sales@gomeasure3d.com
www.gomeasure3d.com