

Safety Data Sheet

according to 29 CFR 1910.1200(g)

AESUB orange

Revision date: 02.06.2021

Page 1 of 10

1. Identification**Product identifier**

AESUB orange

Recommended use of the chemical and restrictions on use**Use of the substance/mixture**

Coatings

Uses advised against

Do not use for products which come into contact with the food stuffs.

Do not use for private purposes (household).

Details of the supplier of the safety data sheet

Company name:	Scanningspray Vertriebs GmbH	
Street:	Johann-Strauss-Str. 13	
Place:	D-45657 Recklinghausen	
Telephone:	+49 (0)176 82 41 39 36	
e-mail:	info@aesub.com	
Contact person:	Max Liese	Telephone: +49(0)231-5868 9271
e-mail:	liese@aesub.com	
Internet:	www.aesub.com	

Emergency phone number:

24 Hour Emergency Contact Phone Number for Chemical Emergency, Spill, Leak, Fire, Exposure or Accident. Call Day and Night within USA and Canada: 1-800-424-9300, outside USA and Canada: 001-703-527-3887

Further Information

Emergency phone number

China: 4001-204937

(CCN 994267 / WISAG FMO Cargo Service GmbH & Co. KG)

2. Hazard(s) identification**Classification of the chemical****29 CFR Part 1910.1200**

Flammable aerosols: Flam. Aerosol 1

Gases under pressure: Compressed gas

Serious eye damage/eye irritation: Eye Irrit. 2A

Respiratory or skin sensitization: Skin Sens. 1

Label elements**29 CFR Part 1910.1200****Signal word:**

Danger

Pictograms:**Hazard statements**

Extremely flammable aerosol

Contains gas under pressure; may explode if heated

May cause an allergic skin reaction

Causes serious eye irritation

Precautionary statements

If medical advice is needed, have product container or label at hand.

Safety Data Sheet

according to 29 CFR 1910.1200(g)

AESUB orange

Revision date: 02.06.2021

Page 2 of 10

Keep out of reach of children.
 Read label before use.
 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
 Do not spray on an open flame or other ignition source.
 Pressurized container: Do not pierce or burn, even after use.
 Avoid breathing dust/fume/gas/mist/vapors/spray.
 Contaminated work clothing must not be allowed out of the workplace.
 Wear protective gloves/protective clothing/eye protection/face protection.
 If on skin: Wash with plenty of Water and soap.
 Specific treatment (see Dispose of waste according to applicable legislation. on this label).
 If skin irritation or rash occurs: Get medical advice/attention.
 Wash contaminated clothing before reuse.
 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.
 Continue rinsing.
 If eye irritation persists: Get medical advice/attention.
 Store in a well-ventilated place.
 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Hazards not otherwise classified

No information available.

3. Composition/information on ingredients**Mixtures****Hazardous components**

CAS No	Components	Quantity
64-17-5	ethanol; ethyl alcohol	17.36 %
287-92-3	cyclopentane	5.26 %
5989-54-8	(S)-p-mentha-1,8-diene; l-limonene	0.0396 %

4. First-aid measures**Description of first aid measures****General information**

When in doubt or if symptoms are observed, get medical advice. Remove victim out of the danger area. Do not leave affected person unattended. Remove contaminated, saturated clothing immediately.

After inhalation

Provide fresh air. If breathing is irregular or stopped, administer artificial respiration. Call a physician immediately.

After contact with skin

Gently wash with plenty of soap and water. Take off contaminated clothing and wash it before reuse. Thaw frosted parts with lukewarm water. Do not rub affected area.

After contact with eyes

Rinse immediately carefully and thoroughly with eye-bath or water. Remove contact lenses, if present and easy to do. Continue rinsing. In case of eye irritation consult an ophthalmologist.

After ingestion

If swallowed, rinse mouth with water (only if the person is conscious). Do NOT induce vomiting. Call a doctor if you feel unwell.

Most important symptoms and effects, both acute and delayed

No information available.

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

Safety Data Sheet

according to 29 CFR 1910.1200(g)

AESUB orange

Revision date: 02.06.2021

Page 3 of 10

5. Fire-fighting measures**Extinguishing media****Suitable extinguishing media**

Water spray, BC-powder
Co-ordinate fire-fighting measures to the fire surroundings.

Unsuitable extinguishing media

Full water jet

Specific hazards arising from the chemical

Extremely flammable aerosol. Pressurized container: May burst if heated. Vapors may form explosive mixtures with air.

In case of fire may be liberated: Carbon dioxide (CO₂), Carbon monoxide, Pyrolysis products, toxic.

Special protective equipment and precautions for fire-fighters

In case of fire: Wear self-contained breathing apparatus. Full protection suit.
In case of fire and/or explosion do not breathe fumes. Fight fire with normal precautions from a reasonable distance.

Additional information

Use water spray/stream to protect personnel and to cool endangered containers. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

6. Accidental release measures**Personal precautions, protective equipment and emergency procedures**

Remove all sources of ignition.

Environmental precautions

Do not allow uncontrolled discharge of product into the environment. Explosion risk.
Retain contaminated washing water and dispose it.

Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

Reference to other sections

Hazardous combustion products: Section 5: Fire-Fighting Measures
Safe handling: see section 7
Personal protection equipment (PPE): see section 8
Disposal: see section 13

7. Handling and storage**Precautions for safe handling****Advice on safe handling**

Provide adequate ventilation.
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not pierce or burn, even after use.

Advice on protection against fire and explosion

Do not spray on naked flames or any incandescent material. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges. Vapors may form explosive mixtures with air.

Further information on handling

Wash hands thoroughly after handling. When using do not eat, drink, smoke, sniff. Used working clothes should not be worn outside the work area.

Conditions for safe storage, including any incompatibilities

Safety Data Sheet

according to 29 CFR 1910.1200(g)

AESUB orange

Revision date: 02.06.2021

Page 4 of 10

Requirements for storage rooms and vessels

Keep/Store only in original container. Keep container tightly closed. Keep in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Hints on joint storage

Keep away from food, drink and animal feedingstuffs.
Do not store together with: Oxidizing agent. Pyrophoric or self-heating substances.

Further information on storage conditions

Do not expose to temperatures exceeding 50 °C/122 °F.

8. Exposure controls/personal protection

Control parameters

Exposure limits

CAS No.	Substance	ppm	mg/m ³	f/cc	Category	Origin
78-93-3	2-Butanone (Methyl ethyl ketone)	200	590		TWA (8 h)	REL
78-93-3	2-Butanone	200	590		TWA (8 h)	REL
		300	885		STEL (15 min)	REL
75-28-5	Butane: isobutane	1000			STEL (15 min)	ACGIH-2020
106-97-8	Butane: n-butane	1000			STEL (15 min)	ACGIH-2020
287-92-3	Cyclopentane	600	1720		TWA (8 h)	REL
		600			TWA (8 h)	ACGIH-2020
74-84-0	Ethane	-	-		Asphyxiant	ACGIH-2020
64-17-5	Ethanol	1000			STEL (15 min)	ACGIH-2020
64-17-5	Ethyl alcohol (Ethanol)	1000	1900		TWA (8 h)	REL
64-17-5	Ethyl alcohol	1000	1900		TWA (8 h)	REL
75-28-5	Isobutane	800	1900		TWA (8 h)	REL
78-93-3	Methyl ethyl ketone	200			TWA (8 h)	ACGIH-2020
		300			STEL (15 min)	ACGIH-2020
106-97-8	n-Butane	800	1900		TWA (8 h)	REL
74-98-6	Propane	1000	1800		TWA (8 h)	REL
		1000	1800		TWA (8 h)	REL
		-	-		Asphyxiant	ACGIH-2020

Biological Exposure Indices (BEI-ACGIH)

CAS No.	Substance	Determinant	Value	Test material	Sampling time
78-93-3	METHYL ETHYL KETONE	Methyl ethyl ketone	2 mg/L	urine	End of shift

Exposure controls



Appropriate engineering controls
Provide adequate ventilation.

Safety Data Sheet

according to 29 CFR 1910.1200(g)

AESUB orange

Revision date: 02.06.2021

Page 5 of 10

Protective and hygiene measures

Take off contaminated clothing. Wash hands before breaks and after work. When using do not eat, drink, smoke, sniff.

Eye/face protection

Wear eye protection/face protection.

Hand protection

Butyl caoutchouc (butyl rubber). Thickness of glove material: 0,7 mm ,penetration time (maximum wearing period): 240min

The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Skin protection

Flame-retardant protective clothing. Wear anti-static footwear and clothing

Respiratory protection

In case of inadequate ventilation wear respiratory protection. Filter type: ABEK-P2

Environmental exposure controls

Avoid release to the environment.

9. Physical and chemical properties**Information on basic physical and chemical properties**

Physical state:	Liquid (Aerosol)
Color:	not determined
Odor:	characteristic
Odour threshold:	not determined
pH-Value:	not determined

Changes in the physical state

Melting point/freezing point:	-187,6 °C
Boiling point or initial boiling point and boiling range:	-161,5 °C
Flash point:	-88,6 °C

Flammability

Solid:	not applicable
Gas:	not applicable

Explosive properties

Extremely flammable aerosol. Heating may cause an explosion.

Lower explosion limits:	1,1 vol. %
Upper explosion limits:	15 vol. %
Auto-ignition temperature:	287 °C

Self-ignition temperature

Solid:	not applicable
Gas:	not applicable

Decomposition temperature: not determined

Oxidizing properties

The product is not: oxidising.

Vapor pressure: 360 hPa
(at 20 °C)

Safety Data Sheet

according to 29 CFR 1910.1200(g)

AESUB orange

Revision date: 02.06.2021

Page 6 of 10

Density:	not determined
Water solubility:	not determined
Solubility in other solvents	
not determined	
Partition coefficient n-octanol/water:	not determined
Viscosity / dynamic:	not determined
Viscosity / kinematic:	not determined
Relative vapour density:	not determined
Evaporation rate:	not determined

Other information

Content of flammable components (%) 92,99

10. Stability and reactivity**Reactivity**

Extremely flammable aerosol. Pressurized container: May burst if heated.

Chemical stability

Stability: Stable

The product is stable under storage at normal ambient temperatures.

Possibility of hazardous reactions

Hazardous reactions: Will not occur

No known hazardous reactions.

Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Protect against direct sunlight.

Do not spray on an open flame or other ignition source.

Incompatible materials

Oxidising agent

Hazardous decomposition productsIn case of fire may be liberated: Carbon dioxide (CO₂), Carbon monoxide, Pyrolysis products, toxic.**11. Toxicological information****Information on toxicological effects****Route(s) of Entry**

Eye contact, oral, dermal, inhalative.

Acute toxicity

Based on available data, the classification criteria are not met.

CAS No	Components				
	Exposure route	Dose	Species	Source	Method
64-17-5	ethanol; ethyl alcohol				
	oral	LD50 mg/kg	10170	Rat	Manufacturer
287-92-3	cyclopentane				
	oral	LD50 mg/kg	> 5000	Rat	Manufacturer OECD 423

Irritation and corrosivity

Safety Data Sheet

according to 29 CFR 1910.1200(g)

AESUB orange

Revision date: 02.06.2021

Page 7 of 10

Causes serious eye irritation

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Sensitizing effects

May cause an allergic skin reaction ((S)-p-mentha-1,8-diene; l-limonene)

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

Specific target organ toxicity (STOT) - single exposure

Based on available data, the classification criteria are not met.

Specific target organ toxicity (STOT) - repeated exposure

Based on available data, the classification criteria are not met.

Carcinogenicity (OSHA): No ingredient of this mixture is listed.

Carcinogenicity (IARC): Ethanol in alcoholic beverages (CAS 64-17-5) is listed in group 1.

Carcinogenicity (NTP): No ingredient of this mixture is listed.

Aspiration hazard

Based on available data, the classification criteria are not met.

Practical experience

Other observations

No information available.

12. Ecological information

Ecotoxicity

The product is not: Ecotoxic.

Persistence and degradability

The product has not been tested.

Bioaccumulative potential

The product has not been tested.

Mobility in soil

The product has not been tested.

Other adverse effects

No information available.

Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

13. Disposal considerations

Waste treatment methods

Disposal recommendations

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Dispose of waste according to applicable legislation.

Contaminated packaging

Handle contaminated packages in the same way as the substance itself.

14. Transport information

US DOT 49 CFR 172.101

<u>UN/ID number:</u>	UN 1950
<u>Proper shipping name:</u>	AEROSOLS
<u>Transport hazard class(es):</u>	2.1
Hazard label:	2.1

Safety Data Sheet

according to 29 CFR 1910.1200(g)

AESUB orange

Revision date: 02.06.2021

Page 8 of 10

**Marine transport (IMDG)**

UN number: UN 1950
UN proper shipping name: AEROSOLS
Transport hazard class(es): 2.1
Packing group: -

Hazard label: 2.1



Marine pollutant: no
 Special Provisions: 63, 190, 277, 327, 344, 381, 959
 Limited quantity: 1000 mL
 Excepted quantity: E0
 EmS: F-D, S-U

Air transport (ICAO-TI/IATA-DGR)

UN number: UN 1950
UN proper shipping name: AEROSOLS, FLAMMABLE
Transport hazard class(es): 2.1
Packing group: -

Hazard label: 2.1



Special Provisions: A145 A167 A802
 Limited quantity Passenger: 30 kg G
 Passenger LQ: Y203
 Excepted quantity: E0
 IATA-packing instructions - Passenger: 203
 IATA-max. quantity - Passenger: 75 kg
 IATA-packing instructions - Cargo: 203
 IATA-max. quantity - Cargo: 150 kg

Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

Special precautions for user

Warning: Extremely flammable aerosol.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

not applicable

15. Regulatory information**U.S. Regulations****National Inventory TSCA**

CAS No. 106-97-8 (butane): Yes.
 CAS No. 74-98-6 (propane): Yes.
 CAS No. 64-17-5 (ethanol; ethyl alcohol): Yes.

Safety Data Sheet

according to 29 CFR 1910.1200(g)

AESUB orange

Revision date: 02.06.2021

Page 9 of 10

CAS No. 110-82-7 (cyclohexane): Yes.
 CAS No. 78-93-3 (butanone; ethyl methyl ketone): Yes.
 CAS No. 75-28-5 (isobutane): Yes.
 CAS No. 287-92-3 (cyclopentane): Yes.
 CAS No. 110-82-7 (cyclohexane): Yes.
 CAS No. 287-92-3 cyclopentane): Yes.
 CAS No. 5989-54-8 ((S)-p-mentha-1,8-diene; l-limonene): Yes.

National regulatory information

SARA Section 304 CERCLA:

Methyl ethyl ketone (78-93-3): Reportable quantity = 5,000 (2270) lbs. (kg)

SARA Section 311/312 Hazards:

Butane (106-97-8): Fire hazard

ethanol; ethyl alcohol (64-17-5): Fire hazard, Immediate (acute) health hazard

Propane (74-98-6): Fire hazard

cyclopentane (287-92-3): Fire hazard, Immediate (acute) health hazard

Isobutane (75-28-5): Fire hazard

Ethane (74-84-0): Fire hazard, Sudden release of pressure

Methyl ethyl ketone (78-93-3): Fire hazard, Immediate (acute) health hazard

(S)-p-mentha-1,8-diene; l-limonene (5989-54-8): Fire hazard, Immediate (acute) health hazard

Clean Air Act Section 112(r):

Butane (106-97-8): Threshold quantities = 10,000 lbs.

Propane (74-98-6): Threshold quantities = 10,000 lbs.

Isobutane (75-28-5): Threshold quantities = 10,000 lbs.

Ethane (74-84-0): Threshold quantities = 10,000 lbs.

Clean Air Act Section 112(b):

Methyl ethyl ketone (78-93-3)

State Regulations**Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65, State of California)**

This product can not expose you to chemicals known to the State of California to cause cancer, birth defects or other reproductive harm.

Additional information

CAS No. 106-97-8 (butane): Yes.

CAS No. 64-17-5 (ethanol; ethyl alcohol): Yes.

CAS No. 74-98-6 (propane): Yes.

CAS No. 287-92-3 (cyclopentane): Yes.

CAS No. 5989-54-8 ((S)-p-mentha-1,8-diene; l-limonene): Yes.

CAS No. 78-93-3 (butanone; ethyl methyl ketone): Yes.

CAS No. 74-84-0 (ethane): Yes.

CAS No. 75-28-5 (isobutane): Yes.

16. Other information**Hazardous Materials Information Label (HMIS)**

Health: *2

Flammability: 4

Physical Hazard: 1

NFPA Hazard Ratings

Health: 2

Flammability: 4

Reactivity: 1

Unique Hazard:

Revision date: 02.06.2021

Revision No: 1,0



Safety Data Sheet

according to 29 CFR 1910.1200(g)

AESUB orange

Revision date: 02.06.2021

Page 10 of 10

Abbreviations and acronyms

ACGIH: American Conference of Governmental Industrial Hygienists
CFR: Code of Federal Regulations
DOT: Department of Transportation
ICAO: International Civil Aviation Organization
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
IARC: International Agency for Research on Cancer
GHS: Globally Harmonized System of Classification and Labelling of Chemicals
CAS: Chemical Abstracts Service
NFPA: National Fire Protection Association
NTP: National Toxicology Program
OSHA: Occupational Safety and Health Administration
PEL: permissible exposure limit
REL: recommended exposure limit
SARA: Superfund Amendments and Reauthorization Act
STEL: Short-term exposure limit
TSCA: Toxic Substances Control Act
TWA: time-weighted average
TI: Technical Instructions
DGR: Dangerous Goods Regulations
UN: United Nations
ATE: Acute toxicity estimate
LC50: Lethal concentration, 50%
LD50: Lethal dose, 50%
LL50: Lethal loading, 50%
EL50: Effect loading, 50%
EC50: Effective Concentration 50%
ErC50: Effective Concentration 50%, growth rate
NOEC: No Observed Effect Concentration
BCF: Bio-concentration factor
MARPOL: International Convention for the Prevention of Marine Pollution from Ships
IBC: Intermediate Bulk Container
VOC: Volatile Organic Compounds

Other data

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)